

# INSTRUCTIONS FOR USE



## Step 1. Add:

- Add a one pound bag into the mix for each yard of concrete to be delayed for up to three hours. The following quantities are based on a standard concrete hopper on the pump and 5 inch lines:

### BOOMS

- Booms 32 meters and below - one bag.
- Booms larger than 32 meters - two bags.

### LINE PUMPS

- For large lines (5 inches) use one bag for each 100 feet.
- For small lines (less than 5 inches) use one bag for each 200 feet.

## Step 2. Agitate:

- Agitate at high speed for five minutes.

## Step 3. Mix:

- If there is concrete in the pump system, please tip hose over hopper and re-circulate so that Slow Willie is completely mixed with all concrete in system and hopper.

## Step 4. Adjustments:

If Slow Willie treated concrete will be used:

- Sooner than planned, add fresh concrete or concrete accelerators.
- Later than planned and has not returned to its original slump, simply add more Slow Willie.

**SIMPLE:** No pre-mixing required

**DELAYS SET:** Delay concrete set for up to three hours.

**SAFE:** No long-term impact on concrete.

**ECONOMICAL:** Minimal expense.

**CHEAP INSURANCE:** Alleviate thousands of dollars in downtime and broken equipment.

**EQUIPMENT-FRIENDLY:** Reduce wear and tear on equipment.

**LABOR SAVER:** Minimize time spent removing hardened concrete.

**INCREASED FLEXIBILITY:** Allow time to reach proper clean-out location.

Remember: The information contained herein is, to the best of our knowledge and belief, accurate. However, since handling conditions and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. Enviro-Systems, Inc.'s responsibility for any claim arising out of breach of warranty, negligence, and strict liability or otherwise is limited to the purchase price of the materials.

1869 South Cobb Industrial Blvd, Ste 30  
Smyrna, GA 30082 USA  
770.333.0206  
800.851.3082  
www.envirosys.us

**ENVIROSYSTEMS**  
Your Concrete Construction Problems, Solved

