

WILLIE SHIELD INSTRUCTIONS



USE...

In order to reduce shipping costs, Willie Shield is shipped in its concentrated form. The dilution ratio is 11:1. Our 5 and 55 gallon packaging has a water level marked on it to make dilution easy. For our 2 liter packaging, please follow the water dilution ratio of 11:1.

- Rinse vehicles or tools prior to application
- Add clean water to the line marked on the container, or dilute as needed
- Agitate or mix to form a white, milky solution
- Spray a thin film of Willie Shield on all parts of the vehicle or equipment that is likely to come in contact with concrete
- Rinse off concrete splatter within 24 hours

RESULTS...

Prevents concrete, grout, and other cementitious material from sticking to surfaces

MAINTAIN...

Re-apply before every job or after every washing

SAFE...

- 100% safe for users
- Non-hazardous and biodegradable

ADVANTAGES...

- Legal and environmentally-safe versus a hydraulic/diesel mixture
- Can be applied with any sprayer. Clean sprayer after use
- Inhibits concrete but is water soluble
- Contains no petrochemicals
- More economical than plan oils
- Can be used as a rust inhibitor
- Used with concrete pumps, ready-mix trucks, screeds, forms, tools, and other surfaces

Disclaimer: The information contained herein is accurate based not only on laboratory results but also on field experience. The responsibility of Enviro-Systems, Inc. for claims arising out of breach of warranty, negligence, and strict liability or otherwise is limited to the purchase price of the Willie Shield used.

1869 South Cobb Industrial Blvd, Ste 30
Smyrna, GA 30082 USA
770.333.0206
800.851.3082
www.envirosys.us

ENVIROSYSTEMS
Your Concrete Construction Problems, Solved

A cartoon illustration of a muscular man with a large nose, wearing a yellow hard hat and a green shirt, with his arms crossed.